ICON DATA VINYL

TECHNICAL DATA SHEET



"Innovative Access Flooring, *Sustainable Solutions*"

ICON DATA VINYL

TECHNICAL DATA SHEET

ICON DATA GERFLOR VINYL SYSTEM

RECOMMENDED APPLICATIONS

DATA CENTRES SERVER ROOMS

SYSTEM DETAILS

SYSTEM NAME:	Icon Data Vinyl
DESCRIPTION:	Icon Data Vinyl is a finished system designed for Computer and Data Centre environments. It can be used for mapping and distributing cabling, data and other electrical services in the subfloor. The Icon Data Vinyl system has a Dissipative Anti-static 0.08in Vinyl surface finish. The Vinyl protects against voltage shorts that can occur with electrical equipment and creates an electrostatic discharge to help prevent buildup of the static electricity which could damage equipment.
LOAD LEVELS:	1000LBS | 1250LBS | 1500LBS | 2000LBS | 2500LBS



ICON PANEL DETAILS

SIZE:	24in x 24in
DEPTH:	1.3in
CONSTRUCTION:	The panels consist of a hardened steel top and bottom sheet plate with corrosion resistant protection, inside and out, encapsulating a structural cementitious core.
CORE:	Cementitious Compound
FINISH:	Gerflor Mipolam Robust EL7 Dissipative Anti-static 0.08in Vinyl surface finish.
TOLERANCE:	±0.01in and a flatness tolerance of ±0.02in measured on a diagonal across the top of the panel
CONNECTION:	The panel is gravity held on top of the stringer assembly.



ICON DATA VINYL

TECHNICAL DATA SHEET

ICON DATA GERFLOR VINYL SYSTEM


ICON DATA PEDESTAL DETAILS

SIZE:	4in x 4in base plate
CONSTRUCTION:	Corrosion resistant galvanized steel pedestal base, head and rod. Aluminium head assembly with locating ABS gasket.
LOCKING:	The pedestals will be provided with an adjusting and locking nut to maintain the assembly at a selected height, which requires a deliberate action to change the height setting, and which prevents vibration displacement.
FINISH:	Corrosion resistant galvanized finish.
CONNECTION:	The panel is screw fixed to the pedestal head at all four corners..
FFH:	The finished floor height of the access floor is measured from the sub floor to the top surface of the installed access floor.



ICON DATA STRINGER DETAILS

SIZE:	24in
CONSTRUCTION:	Rectangular steel welded tube with 0.06in sponge rubber foam.
FINISH:	Corrosion resistant galvanized finish with 0.06in sponge rubber foam.
CONNECTION:	The stringer is screw fixed into the pedestal head.



ICON DATA VINYL

TECHNICAL DATA SHEET

ICON DATA GERFLOR VINYL SPECIFICATIONS AND TESTING

CISCA RECOMMENDED TEST PROCEDURES

ASP Access Floor systems are independently tested in accordance with the CISCA Recommended Test Procedures for Access Floors, the recognised performance standard for raised access flooring throughout North America. These test procedures evaluate structural performance, rolling load durability, pedestal stability, impact resistance and system serviceability, providing confidence that every ASP access floor system delivers reliable performance in demanding commercial and mission-critical environments.

TEST TYPE	STANDARD	DESCRIPTION
STRUCTURAL	CISCA Section 1	Concentrated Load
STRUCTURAL	CISCA Section 2	Ultimate Load
STRUCTURAL	CISCA Section 3	Rolling Load
STRUCTURAL	CISCA Section 4	Stringer Uniform Load
STRUCTURAL	CISCA Section 5	Pedestal Axial Load
STRUCTURAL	CISCA Section 6	Pedestal Overturning Moment
STRUCTURAL	CISCA Section 7	Panel Drop Test
STRUCTURAL	CISCA Section 8	Impact Load Test
STRUCTURAL	CISCA Section 9	Panel Cut-Out Test

ICON DATA VINYL

TECHNICAL DATA SHEET

ICON DATA GERFLOR VINYL SPECIFICATIONS AND TESTING

ICON DATA VINYL PERFORMANCE RESULTS

Tested as per CISCA Recommended Test Procedures

CONCENTRATED LOAD	1000LBS	1250LBS	1500LBS	2000LBS	2500LBS	3000LBS
ULTIMATE LOAD	6500LBS	7500LBS	9500LBS	10,100LBS	10,800LBS	11,150LBS
UNIFORM LOAD	486.6 lb/ft^2	691.3 lb/ft^2	889.7 lb/ft^2	1040 lb/ft^2	1217.6 lb/ft^2	1397.2 lb/ft^2
IMPACT LOAD	150LBS	150LBS	150LBS	150LBS	150LBS	200LBS
PANEL WEIGHT (LBS)	32	34.8	36.6	41.9	42.8	46.8
SYSTEM WEIGHT (LBS/ft^2@ 18in FFH)	9.6	10.2	10.5	11.8	12.4	12.4

ICON DATA VINYL DYNAMIC ROLLING RESULTS

Tested as per CISCA Recommended Test Procedures

WHEEL SIZES/CYCLES	1000LBS	1250LBS	1500LBS	2000LBS	2500LBS	3000LBS
3 x 1.2 in (10 PASSES)	800LBS	1000LBS	1250LBS	1500LBS	2000LBS	2400LBS
6 x 2 in (10,000 PASSES)	670LBS	800LBS	1000LBS	1250LBS	1600LBS	2000LBS

ICON DATA VINYL

TECHNICAL DATA SHEET

ICON DATA GERFLOR VINYL SPECIFICATIONS AND TESTING

PERFORMANCE TESTING

TEST TYPE	STANDARD	RESULT
FIRE	BS 476-4 Non-combustibility test	Non-combustible
FIRE	EN-13501-1 European Fire Classification System	A1fl
FIRE	ASTM E84 Surface Burning Characteristics (Flame spread and smoke development)	Class A
FIRE	ASTM E119 Fire Resistance of Complete Building Assemblies	Integrity 60mins / Insulation 23mins
FIRE	EN ISO 1182 Non-Combustibility Test	Pass
FIRE	EN ISO 1716 Heat of Combustion Test	Pass
FIRE	ISO 9239.1 Mean Distance of Flame Travel	30 mm
FIRE	ISO 9239.1 Average Critical Radiant Flux	≥11.5kW / m^2
FIRE	ISO 9239.1 Average Integrated Smoke Value	11% x min
INDOOR AIR QUALITY	CDPH Standard Test Method v1.2 (California Section 01350)	Pass
INDOOR AIR QUALITY	ASTM D5116 Environmental Chamber VOC Test	Pass
ACOUSTIC	ASTM E492-09 Impact Sound Transmission	IIC 60
ACOUSTIC	ISO 10140-3 Laboratory Measurement of Impact Sound Insulation	Ln,w 40 dB
ASBESTOS	NIOSH9002 Bulk Asbestos Analysis	Not detected
SLIP RESISTANCE	DIN 51130:2014-02 Slip Resistance (oil-wet ramp test)	R9
SALT SPRAY TEST	ASTM B117-18 Neutral Salt Spray Test	Pass – No corrosion
HEALTH & SAFETY	Respirable Crystalline Silica Analysis	Laboratory Tested

ICON DATA VINYL

TECHNICAL DATA SHEET

ICON DATA GERFLOR VINYL SPECIFICATIONS AND TESTING

PERFORMANCE OF SURFACE FINISH

Gerflor theflooringgroup	MIPOLAM ROBUST EL7		
DESCRIPTION			
Total thickness	EN ISO 24346	mm	2.00
Weight	EN ISO 23997	g/m²	3300
Width of sheet	EN ISO 24341	cm	200
Length of sheet	EN ISO 24341	lm	20
Tile size	EN ISO 24342	mm	608 x 608
Number of tiles per package		-	20
CLASSIFICATION			
Standard / Product specification	-	-	EN ISO 10581
European classification	EN ISO 10874	class	34 - 43
Fire rating	EN 13501-1	class	B_{fl}-s1
Electrical resistance (1)	EN 1081	Ohm	10^6 :s Rt :s 10^8
Electrical resistance	ASTM F 150	Ohm	10^6 :s Rt :s 10^9 (2)
Static electrical propensity	EN 1815	kV	< 2
PERFORMANCE			
Type Binder content	EN ISO 10581	type	II
Dimensional stability	EN ISO 23999	%	sheet :s 0.40 tile :s 0.25
Residual indentation (norm)	EN ISO 24343-1	mm	≤ 0.10
Residual indentation (average measured value)	-	mm	~ 0,03
Castor chair test (type W)	ISO 4918	-	OK
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN ISO 26987	-	OK
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/ m³	< 10
CE MARKING			
CE	EN 14041	-	<10⁹Ω DS
		-	B_{fl}-s1

(1) Measured before installation
(2) If RH level is > 40%

ICON DATA VINYL

TECHNICAL DATA SHEET

ICON DATA GERFLOR VINYL COLOUR HUB

VINYL COLOUR HUB

ICON DATA VINYL

TECHNICAL DATA SHEET

ICON DATA GERFLOR VINYL LOAD GUIDELINES

Access floors may need to support the movement of heavy loads both during construction and after the space is in use. During construction, this can include transporting materials, tools and equipment across the floor. In a finished environment, it can include moving furniture, machinery or other equipment into place or even cleaning and maintenance procedures.

The guidelines below provide recommended unit loads and maximum total loads for each concentrated load rating, with separate values for travel with and without protection. Use them when planning how loads will be moved across the floor, taking into account the combined weight of the unit, operator and any materials being transported. Where protection is used, a suitable structural substrate must be installed along the entire path of travel.

Concentrated Load Rating	Surface Protection – Recommended Unit Load*	Surface Protection –Maximum Total Load*	Structural Protection – Recommended Unit Load*	Structural Protection – Maximum Total Load*
1,000 lb	1,000 lb	1,100 lb	1,980 lb	2,090 lb
1,250 lb	1,490 lb	1,710 lb	2,430 lb	2,650 lb
1,500 lb	1,980 lb	2,200 lb	2,980 lb	3,200 lb
2,000 lb	2,470 lb	2,910 lb	3,260 lb	3,700 lb
2,500 lb	3,020 lb	3,460 lb	3,790 lb	4,230 lb

**Loads include the unit, operator and any materials being transported. "Surface Protection" requires light surface protection such as coreflute or foam. "Structural protection" requires a suitable structural substrate to be installed along the entire path of travel.*

ICON DATA VINYL

TECHNICAL DATA SHEET

ICON DATA GERFLOR VINYL SUSTAINABILITY CREDENTIALS

ORGANIZATIONAL COMMITMENTS

- ASP Environmental Policy ✅
- ISO 14001 ✅
- ISO 9001 ✅
- ISO 45001 ✅

INDOOR AIR IMPACTS

- VOC Emission Compliance Testing ✅



ICON DATA VINYL

TECHNICAL DATA SHEET

ICON DATA GERFLOR VINYL MAINTENANCE

MAINTENANCE GUIDE

CLEANING:

Remove dust and construction debris using a vacuum cleaner. Avoid sweeping the floor surface, as fine dust can migrate between panel joints and onto pedestal heads or stringers, potentially resulting in unwanted noise or reduced system performance.

PANEL REMOVAL & REINSTALLATION:

Only remove panels using an approved ASP panel lifting device.

Lift panels vertically to avoid damage to adjacent panels and pedestal heads

After maintenance beneath the floor, ensure each panel is correctly seated and securely fastened before returning the floor to service.

UNDERFLOOR ACCESS:

When carrying out maintenance to underfloor services:
- Remove only the minimum number of panels required.
- Avoid placing excessive loads on unsupported panels.
- Inspect pedestal heads and fasteners before reinstalling panels.
- Remove any debris from the underfloor plenum before replacing panels.

HEAVY LOADS:

Heavy equipment shall not be moved across the access floor without suitable load-spreading protection. Refer to ASP for allowable rolling loads and recommended floor protection.

SITE CONDITIONS:

During construction and throughout the service life of the floor, excessive dust, moisture and debris should be prevented from accumulating beneath the access floor. Maintaining a clean underfloor plenum will assist in preserving long-term system performance and minimising the potential for unwanted noise.

REPLACEMENT COMPONENTS:

Replacement panels and accessories should be supplied by ASP Access Floors to ensure compatibility with the installed system.



ASP

ACCESSFLOORS

www.aspfloors.com